

Product										
Model:	天之眼-100HD	天之眼-360HD	BB-1MDOMESD	KT-2MDOME	KT-360FishEYEL1.3	KT-2MODPOE	KT-2MOD14VZ	KT-2MODDOME	KT-2MODPTZ	
Image Sensor	1/4" OV9712A CMOS Sensor	1/4" OV9712A CMOS Sensor	1/4" OV9712A CMOS Sensor	1/4" OV9712A CMOS Sensor	1/4" OV9712A CMOS Sensor	1/4" OV9712A CMOS Sensor	1/4" OV9712A CMOS Sensor	1/2.8" SONY323	1/2.8" SONY323	1/2.8" SONY323
Max. Resolution	720P	720P	720P/ 1080p	1080p	960P	1080P	1080P	1080P	1080P	1080P
Lens	2.8mm	2.8mm	2.8mm	2.8mm	1.2mm	3.6mm	2.8 - 12mm	2.8 - 12mm	2.8 - 12mm	2.8 - 12mm
View Angle	98.1°	98.1°	98.1°	98.1°	355°	80°	31 ~ 97.8°	31 ~ 97.8°	31 ~ 97.8°	31 ~ 97.8°
Min.illumination	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux
IR LED/Effective Range	~10m	~20m	~25m	~25m	~20m	~25m	~25m	~25m	~25m	~50m
Compression	H.264	H.264	H.264	H.264	H.264	H.264	H.264	H.264	H.264	H.264
Edge Recording	64GB	32GB	32GB / NA	-	-	optional	optional	-	optional	
Interface	-	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45	10/100 Base-T, RJ-45
Concurrent Users	5	5	5	5	5	5	5	5	5	
Support moblie platforms	iphone/android	iphone/android	iphone/android	iphone/android	iphone/android	iphone/android	iphone/android	iphone/android	iphone/android	
ONVIF	Profile S	Profile S	Profile S	Profile S	Profile S	Profile S	Profile S	Profile S	Profile S	
Alarm Input	-	2x	-	-	-	-	-	-	-	
Motion Detection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Action	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	Recording, alarm output upload to FTP, emails snapshot	
Input	Built in Mic	Built in Mic	1x	1x	1x	1x	1x	1x	1x	
Qutput	Built in speaker	Built in speaker	1x	1x	1x	1x	1x	1x	1x	
Power	DC 5V (1500 mA)	DC 5V (2500 mA)	DC 12V (750 mA)	DC 12V (750 mA)	DC 12V (750 mA)	PoE / DC 12V (1000 mA)	PoE / DC 12V (1000 mA)	PoE / DC 12V (1000 mA)	PoE / DC 12V (1000 mA)	
Protection	-	-	-	-	-	IP66	IP66	IP65	IP66	
Ambient Temperature	-15°C ~ +50°C	-15°C ~ +50°C	-15°C ~ +50°C	-15°C ~ +50°C	-15°C ~ +50°C	-15°C ~ +50°C	-15°C ~ +50°C	-15°C ~ +50°C	-15°C ~ +50°C	
Relative Humidity	90% (no condensation)	90% (no condensation)	90% (no condensation)	90% (no condensation)	90% (no condensation)	90% (no condensation)	90% (no condensation)	90% (no condensation)	90% (no condensation)	
Net Weight(g)	~280	~450	~450	~450	~450	~500	~600	~800	~1800	